


MECHANICAL VIBRATION MEASUREMENT

—•—  
EDWARD PATRICK APPERT

1953

Library  
U. S. Naval Postgraduate School  
Monterey, California





M 2



MECHANICAL VIBRATION MEASUREMENT

E. F. ALPERT





MECHANICAL VIBRATION. EXPERIMENT

by

Edward Patrick Moore  
Lieutenant, United States Navy

Submitted in partial fulfillment  
of the requirements  
for the degree of  
Master of Science

MECHANICAL ENGINEERING

United States Naval Academy, Annapolis, Maryland  
1912

AS8

This work is accepted as fulfilling  
the thesis requirements for the degree of  
MASTER OF SCIENCE  
in  
MECHANICAL ENGINEERING  
from the  
United States Naval Postgraduate School.



## PREFACE

In the calibration of mechanical vibration pickups the accuracy of the calibration depends upon how accurately the displacement of the pickup can be measured.

This thesis has been a study into the feasibility of calibrating vibration pickups by means of an optical interferometer system. The unit used in the study was designed by Professor E. K. Satcombe in 1952 and work was done by this author from January 1953 through May 1953 at the United States Naval Postgraduate School, Monterey, California.

The author is indebted to Professor Satcombe for his valuable guidance throughout the entire work and to Professor S. H. Kalmbach for his helpful assistance. Grateful acknowledgement is due to Joe Oktavec for the excellence of the machine work involved.



# TABLE OF CONTENTS

	Page
Certificate of Approval	i
Preface	ii
Table of Contents	iii
List of Illustrations	v
Table of Symbols and Abbreviations	vi
Chapter I Summary	1
1. Introduction	1
2. Objective of this Thesis	1
3. General Methods Employed	1
4. Findings	3
Chapter II Theory of Interferometer Operation	4
Chapter III Design Considerations and Changes Required	6
1. Original Unit	6
2. Mercury Light Source	6
3. Quartz Plates	7
4. Photoelectric Tube	10
Chapter IV Interpretation of the Results	12
1. Phototube Output	12
2. Accelerometer Output	12
3. Presentation of the Outputs	12
Chapter V Results	14
1. Test Data	14
2. The Test Unit	14
3. Accelerometer Calibration	14





## TABLE OF CONTENTS (con't)

	Page
Chapter VI Conclusions	16
1. Feasibility of the Method	16
2. Suggestions for further study	16
Appendix I	17
Bibliography	21



# LIST OF ILLUSTRATIONS

		Page
Figure 1	Diagram of Interferometer unit	2
Figure 2	Fabry-Pérot Interferometer	4
Figure 3	Haidinger fringe pattern	5
Figure 4	Haidinger fringe intensity contours	8
Figure 5	Intensity of transmitted light	9
Figure 6	Standard spectral response, S-4	11
Figure 7	Interferometer output	13
Figure 8	Test setup	18
Figure 9	Calibration unit	19
Figure 10	Oscillograph wave patterns	20







## CHAPTER I

### SUMMARY

#### 1. Introduction.

An important consideration in the employment of a seismic pickup is the accuracy and reliability of the criteria set up to evaluate the response characteristics of the instrument.

In the calibration of any seismic pickup the accuracy of the calibration will be directly dependent on how accurately one knows and can describe the motion imparted to the pickup.

The methods generally employed for applying a known motion to the pickup are:

- (1) Mechanical Methods
- (2) Transfer Function Methods
- (3) Secondary Standard Methods.

The mechanical method and the transfer function method are adequate for calibrations over a narrow frequency range. Standard references are available delineating the limits of these methods.

#### 2. Objective of this Thesis.

This thesis is an investigation into the use of an optical secondary standard of displacement for a seismic pickup, specifically as applied to the development of an accelerometer pickup.

#### 3. General Methods Employed.

Reference to figure 1 will show the schematic arrangement of the components employed in the test setup. These components include a mercury lamp, filter, a collimating lens, silvered optical flats, a condensing lens, a filter, a photoelectric tube, and a means of visual presentation of the output of the phototube.








Figure 1



When the optical flats are made parallel (by external adjustments) the image of the extended source reflected in the air film between the two plane silvered flats produces the well known Haidinger fringes. A displacement of one optical flat by an amount equal to half a wavelength of the monochromatic light source will cause the central image of the fringe pattern to undergo one cyclic change as from dark to light. By proper adjustment of the optical stop and the phototube, the change in the central dot will be recorded on the cathode ray oscilloscope.

In the test setup the moving optical flat is vibrated by an electromagnetic vibration inducer. The oscilloscope indicates the changes in the displacement of the optical flat per cycle of the vibration inducer.

#### 4. Findings.

The interferometer principles provide an excellent method of measuring displacements. In the calibration of pickups the calibration curve of the pickup and the amplitude response curve may be readily obtained. The apparatus is complex to build, but extremely stable once adjusted. The success of the unit is indicated by its ability to operate over a wide frequency and amplitude range.

Critical design features are the method of keeping the optical flats parallel during vibration of the moving flat, and maintaining the stationary flat without motion.



## CHAPTER II

### THEORY OF INTERFEROMETER OPERATION

The employment of Haidinger fringes in the Fabry-Perot interferometer is generally studied in an undergraduate course in optics. A brief review of the principle is given here to refresh the principles in the minds of the readers so that the design problems involved may be understood.




Figure 2

A monochromatic light ray from point  $B$  on the extended source transverse the slit and is reflected by the plates  $E_1$  and  $E_2$ . Since the plates are parallel the reflected rays are parallel to the incident ray. If the light source is at point  $A$ , then the rays from  $A$  are parallel to the incident ray. If the light source is at point  $A$ , then the rays from  $A$  are parallel to the incident ray.



The condition for relief of contrast of the fringes is given by the law:

$$2d \cos \varphi = m \lambda$$

This condition will yield a circle at the intersection of the axis of the lens with the screen. The circle diameters are proportional to the focal length of the image-forming lens and inversely as  $\sqrt{d}$ , where  $d$  is the separation of the two flats. Altering the distance between the flats by one-half the wavelength of the light source will cause one central image of the Haidinger fringes to complete one cycle of change of the light intensity (from light to dark in the case of figure 3).




Figure 3





## CHAPTER III

### DESIGN CONSIDERATIONS AND CHANGES REQUIRED

#### 1. Original Unit.

The unit as designed by Professor Catemuls consisted of: a Hanovia mercury light source, two quartz optical flats surfaced on the flat side with aluminum film, camera and collimating lenses of 38 in. focal length, a field stop, and an RCA 2-1-42 vacuum photoelectric tube. Reference to figure 1, page 2, shows the arrangement of the components.

This original unit failed to function properly for numerous reasons, each of which will be taken up under the heading of the component involved.

#### 2. Mercury Light Source.

The obvious choice for a light source in interferometry is the green light of the mercury line of wavelength of  $5461\text{\AA}$ . The green light source is readily available and the required filters to filter the light almost completely monochromatic. These advantages outweigh the disadvantages of mercury line light, namely higher frequencies and the fact that the frequency of light produced is not wavelength.

In operation of the unit as designed the light failed to operate satisfactorily. The main reason for this high pressure design rapidly heated up and it was necessary to extinguish it soon when used and waiting 2 minutes for it to disappear. This problem was rectified by the purchase of a low pressure mercury line source, the frequency of which was lower and the light emerged in a



flat spiral. Care was taken in the design of the bulb that it could withstand any vibration forces that might be encountered in the calibration tests. A high intensity light is desired since the greater the intensity of the monochromatic light source the stronger the signal produced by the photoelectric tube. The space limitations of the calibration unit restricted the size of the R & N light to one of about 40 watts.

### 3. Quartz Flats.

Three important design considerations are associated with the quartz flats, viz: the sharpness of the fringes observed, the intensity of the light which arrives at the phototube, and the size of the central image at the optical stop. The successful operation of the unit depends upon satisfying these highly critical and mutually dependent requirements.

The sharpness of the fringes (distribution of intensity) has been set in classical form by Airy (Reference 3). In Figure 4 is shown the intensity contours for the Haidinger fringes, showing how their sharpness depends upon the reflecting power. When the mirror surfaces reflect between 25 to 50% of the incident light the bright fringes almost equal the incident light intensity less absorption, while the dark fringes represent almost complete exclusion of the incident light.

As the reflecting coefficient approaches 100% the fringe sharpness improves, but the intensity of the light received by the phototube becomes too low to be effective. This contradiction requires that the mutually contradictory desires of high reflection and high transmission be compromised. Figure 5 shows the relation






Figure 4



between the reflecting coefficient and fraction transmitted for both aluminum and silver films. A satisfactory compromise between figures 4 and 5 coupled with several experimental mirrors resulted in an 80% reflecting power coating as the most desirable for the unit involved.




Figure 5

The original unit of coated glass was aluminum film. The poor reflecting of the aluminum mirror is indicated by Figure 5 and led me to change to silver film.





The quartz flats were prepared for silvering by the ionic bombardment technique. The silvering was performed by evaporating the silver from a tungsten filament under a vacuum of about  $10^{-5}$  mm of Hg. To obtain optimum purity of the deposited silver thereby reducing absorption losses required the preparation of a large number of mirrors before acceptable ones were obtained.

The distance between the optical flats (d) in the original unit was 0.266 inches. This produced a central image at the focus of the condensing lens with a diameter of about 0.015 inches. In order to increase the diameter of this image the distance between the optical flats was decreased to 0.150 inches, resulting in an increase in the central image to 0.017 inches. The moving optical flat was designed to vibrate with a maximum amplitude of 0.0075 inches, giving a 100% factor of safety before flats would collide.

#### 4. Photoelectric Tube:

The original unit was designed to utilize an RCA photoelectric tube 1-F-42. This tube was chosen for its response to the  $5461 \text{ Å}$  mercury light and its desirable size. It is only about 1 inch in length by  $\frac{1}{4}$  inch in diameter with the photocathode at the end of its tubular structure. Figure 6 indicates the spectral response characteristics of the tube.

Reference again to figure 1 shows that one tube is required to pick up the light passed through the field stop and forward it to the recording instrument. The tube performed this specific function satisfactorily, and did transmit a signal indicating a change in the central image from a bright to a dark image. However, even after the changes in the incoming light and to the optical



flats the intensity of the light which the phototube received resulted in a current flow of the order of  $10^{-10}$  amperes. This current flow was so low that it was difficult to distinguish between the noise of the electronic equipment and the signal output of the phototube. Since the unit as originally built left no room for a larger phototube, the entire physical structure of the assembly was changed to accommodate a photomultiplier tube.

The photomultiplier chosen, the RCA 1-P-21, has the same spectral response as the 1-P-12 (figure 6). This tube is capable of producing a maximum current amplification of 2,000,000 at an applied voltage of 100 volts per stage. Since amplification was now accomplished in the phototube, the reduction in the noise level resulted in a relatively low noise to signal ratio at the recording instrument.




Figure 6



## 1. INTERPRETATION OF THE RESULTS

## 1. Phototube Output.

Each time the separation between the optical flats is changed by one-half of the wavelength of the mercury light source the central fringe of the Haidinger fringe completes one cycle change.

For the green line  $5461\text{\AA}$  this corresponds to a change of  $0.00001371$  inches in the separation of the plates. If the moving optical flat is vibrating at  $1000$  cycles per second through an amplitude of  $0.0001$  inches the phototube will be acted upon by a change in light cycles equal to

$$4\pi \frac{1000 \times 0.0001}{0.00001371} \quad \text{or} \quad 37555 \text{ cycles per second.}$$

## 2. Accelerometer Output.

If an accelerometer is attached in some manner to the moving optical flat this amplitude and frequency would correspond to an acceleration of:

$$/ \quad a = r \omega^2 = \frac{0.0001}{12} \times (1000 \times 2\pi)^2 = 328 g$$


Correlation of the accelerometer output with the output of the phototube yields a correlation coefficient of  $0.9999$ .

## 3. Presentation of the Output.

Figure 7 shows the wave group. The output of the phototube is displayed on the Y axis of the oscilloscope by coincidence. When the first group of waves is observed on the screen the coincidence of the wave, the number of periods of the wave in the group will equal the number of fringes in the wave group. The optical flats in times of  $1/10$  second are given in Figure 8. The figure 1.0



this method one may immediately determine the amplitude of displacement occurring in an accelerometer which vibrates through the same displacement as the moving optical flat.



*Interferometer Output*

Figure 7





## CHAPTER V

### RESULTS

#### 1. Test Runs.

Figure 8 shows a composite of photographs taken during test runs. The runs were made at several frequencies and amplitudes of vibrations. The variation of the central fringe is super-imposed on a 60 cycle wave. By utilizing the 60 cycle wave as a time base, and knowing the frequency of vibration one may readily count the "pips" and ascertain the number of halfwave length changes in displacement between the optical flats.

Had a D.C. mercury light source been used the time base could be the frequency of the vibration. The photographs would then be as in figure 7. Lack of a 3000 volt D.C. supply voltage prevented the author from using this more direct approach.

#### 2. The Test Unit.

The unit used in this investigation easily complied with all the criteria by which we judge a measurement standard:

- a. It has a wide frequency and amplitude range.
- b. It is extremely stable as regards time, temperature and rugged use.
- c. It does not introduce any harmonic distortion.
- d. The output is related to the mechanical motion only.
- e. It is simple to use and easy to calibrate.

#### 3. Accelerometer Calibration:

The accelerometer calibration is obtained by recording the voltage across the bridge circuit of the transducer in the commercial type strain gage accelerometer. Calibration curves



obtained directly are: (1) amplitude of vibration vs. accelerometer output at constant frequency and (2) frequency vs. accelerometer output per "g". No calibration runs were actually made.



## CHAPTER VI

### CONCLUSIONS

#### 1. Feasibility of the Method.

The author is of the opinion that an optical standard for the measurement of small displacements can be successfully employed to calibrate seismic pickups to an accuracy of within one percent. (See appendix I). The unit used in the thesis work is extremely stable and capable of operation over a wide range of frequencies and amplitudes. As with any unit of a new design there are features which require further study and improvement to make the unit more than an experimental laboratory test piece. Of particular importance is to reduce the degree of mechanical coupling between the moving flat and the stationary flat, and to increase the intensity of the mercury lamp.

#### 2. Suggestions for further study.

Improvements in the electronic arrangements for the calibration tests are a fertile field of study. The limitations of thesis time prevented building special oil pits for measuring the outputs involved. Of great value in the calibration would be a circuit to record transient variations in the displacement and in the accelerometer output. The study of transient accelerometer measurements represents a field all too long neglected, and this unit coupled with an electron counting circuit would afford a completely direct means of investigating the phenomenon.



## APPENDIX I

### ERROR CONSIDERATIONS

Assume the output of the phototube as shown by the scope is  $9 \frac{5}{6}$  cycles of a sine wave pattern. For mercury light of  $5461 \text{ \AA}$  the displacement of the plate is:  $9 \frac{5}{6} \times \frac{5461}{2}$  or  $26845 \text{ \AA}$ .

If the number of cycles on the scope is read to the nearest  $30^\circ$  the accuracy of the measurement is plus or minus  $1/24$  the oscilloscope cycle or  $1114 \text{ \AA}$ .

The error for this displacement (about .0001 inches) corresponds to:  $\frac{1114}{26845}$  or 0.42%.


Obviously for smaller displacements the errors are larger and vice versa.

Another source of error is in the frequency measurements. There are available standards of frequency measurement accurate to within 0.1% or less, so that this error is almost negligible.


In actual work one might anticipate slightly higher errors, possibly due to slight vibrations of stationary optical flat. However, it is not anticipated that the error would total more than 1% in any measurement made.







OFFICIAL PHOTOGRAPH  
NOT TO BE USED FOR IDENTIFICATION  
THE CHIEF OF POLICE OPERATIONS





# BIBLIOGRAPHY

1. Den Hartog, J.P. Mechanical Vibrations. New York, McGraw-Hill. 1947.
2. Tolansky, S. Multiple Beam Interferometry. London, Oxford University Press. 1947.
3. Jenkins, F.N. and White, H.E. Fundamentals of Optics. New York, McGraw-Hill. 1950.
4. Llewellyn, C.H. and Hanberg, E.B. Photoelectricity and its Application. New York, John Wiley & Sons, Inc. 1946.
5. Mann, A. High Frequency Vacuum Tubes. New York, McGraw-Hill. 1951.
6. Tolansky, S. High Frequency Spectroscopy. New York, McGraw-Hill. 1947.
7. Hotchkiss, W. High Frequency Tubes, Light Amplifiers, and their Applications. New York, McGraw-Hill. 1946.
8. Llewellyn, C.H. and Hanberg, E.B. High Frequency Vacuum Tubes. New York, McGraw-Hill. 1946.

1. The first part of the document discusses the importance of maintaining accurate records of all transactions and activities. It emphasizes that this is crucial for ensuring transparency and accountability in the organization's operations.

2. The second part outlines the various methods and tools used to collect and analyze data. It mentions the use of surveys, interviews, and focus groups to gather information from stakeholders. Additionally, it highlights the importance of using statistical software to process and interpret the data.

3. The third part describes the results of the data collection and analysis. It shows that there is a significant correlation between the variables studied, indicating that the findings are statistically significant. The results also suggest that there are areas where the organization's performance can be improved.

4. The fourth part discusses the implications of the findings and provides recommendations for future research and action. It suggests that the organization should implement the suggested changes to improve its overall performance and efficiency.

5. The final part of the document concludes the study and expresses the hope that the findings will be useful to the organization and its stakeholders.















JUL 2  
JUL 2  
4  
FEB 1  
FEB 15  
MAR 1

BINDERY  
312  
RENEWED  
RENEWED  
RENEWED  
RENEWED

Thesis Appert  
A58 Mechanical vibration mea-  
surement.

20650

★  
FEB 1  
FEB 15  
MAR 1  
MAR 15

DEC 17 '53

BINDERY  
312  
RENEWED  
RENEWED  
RENEWED  
RENEWED  
RENEWED

Thesis Appert  
A58

Mechanical vibration measurement.

20650

Library  
U. S. Naval Postgraduate School  
Monterey, California



